49441 Molded Cable Assemblies - Modular Keyboard Assembly



For more information please call

1-800-Belden1

See Put-ups and Colors

Description:

6-position modular retractile, used to rapidly interconnect electronic computers and business machines, polypropylene insulation, unshielded, polyurethane jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	6
Total Number of Conductors	6
Number of Pins	6
AWG	26
Stranding	19x38
Conductor Diameter	.51 in.
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PP - Polypropylene
Nom. Insulation Wall Thickness	0.006 in.

OUTER SHIELD:

Outer Shield Material	Unshielded

OUTER JACKET:

Outer Jacket Material	PUR - Polyurethane
Outer Jacket Nominal Wall Thickness	0.03 in.

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.093 x .258 in.

ASSEMBLY DIMENSIONAL CHARACTERISTICS:

Assembly Dimensional for Retractile Coil Body Length (relaxed)	15 in.
Assembly Dimensional For Retractile Coil Body Length (extended)	67.5 in.
1st End Tail Length	1.5 +/- .5 in.
2nd End Tail Length	1.5 +/- .5 in.

CONNECTOR CHARACTERISTICS:

49441 Molded Cable Assemblies - Modular Keyboard Assembly

FIRST END :	
Connector Characteristics - First End Connector Type	Modular
Connector Characteristics - First End # of Connector Contacts/positions	6
SECOND END :	
Connector Characteristics - Second End Connector Type	Modular
Connector Characteristics - Second End # of Connector Contacts/positions	6
Wiring	Cross Wired. Brown: pin1(E1) to pin 6(E2), Red: pin2(E1) to pin5(E2), Orange: pin3(E1) to pin4(E2), Yellow: pin4(E1) to pin3(E2), Green: pin5(E1) to pin2(E2), Blue: pin6(E1) to pin1(E2)

WIRING DIAGRAM:

Wiring Diagram Color Code Chart :

Number	Color
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue

MECHANICAL CHARACTERISTICS:

UL Temperature Rating	60°C (UL AWM Style 20197)

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

AWM Specification	UL Style 20197 (30 V 60°C) (cable only)

APPLICABLE STANDARDS:

EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

PLENUM/NON-PLENUM:

Plenum (Y/N)	N

ELECTRICAL CHARACTERISTICS:

Max. Operating Voltage - UL	30V (UL AWM Style 20197)

NOTES:

Notes	Positive locking latch prevents connector from vibrating loose. Polarized connector prevents improper insertion. No tools required for installation.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
49441 010B1	6 POS MOD RET CABLE RI47851	B1	0.196	BLACK	Q

49441 Molded Cable Assemblies - Modular Keyboard Assembly

49441 010S2	6 POS MOD RET CABLE RI47851	S2	0.44	BLACK	

Q = STANDARD PACKAGES CANNOT BE BROKEN.

Revision Number: 1 Revision Date: 06-21-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.
All sales of Belden products are subject to Belden's standard terms and conditions of sale.
Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.